


Teollisuus nosto-ovet nostotavat, 40 mm ovipaneelit

TRACK SYSTEM


NP normal



B max	= 8000 mm
bk min	= 100 mm
b min	= 140 mm
bc min	= 260 mm
bn min	= 270 mm
bp min	= 190 mm
H max	= 5510 mm = 7000 mm
Hn min	= 450 mm = 510 mm
Hp	= H - 50 mm
Hpn	= H
W min	= H + 675 mm
BxH max	= 41 m ²

LHRF low

with front mounted springs



B max	= 8000 mm
bk min	= 100 mm
b min	= 140 mm
bc min	= 260 mm
bn min	= 270 mm
bp min	= 190 mm
H max	= 5000 mm
Hn min	= 320 mm
Hp	= H - 150 mm
Hpn	= H - 50 mm
W min	= H + 330 mm
BxH max	= 32 m ²

LHR low

with back mounted springs



B max	= 6000 mm
bk min	= 160 mm
b min	= 160 mm
bc min	= 280 mm
bn min	= 290 mm
bp min	= 210 mm
H max	= 5000 mm
Hn min	= 180 mm
Hp	= H - 200 mm
Hpn	= H - 130 mm
W min	= H + 1100 mm
BxH max	= 20 m ² (28m ²)

LHR-B low


with back mounted springs



B max	= 8000 mm
bk min	= 160 mm
b min	= 160 mm
bc min	= 280 mm
bn min	= 290 mm
bp min	= 210 mm
H max	= 5000 mm
Hn min/max	= 180/245 mm
Hp	= H - 200 mm
Hpn	= H - 130 mm
W min	= H + 1100 mm
BxH max	= 20 m ² (28m ²)


FTR normal

along roof construction




B max	= 8000 mm
bk min	= 100 mm
b min	= 140 mm
bc min	= 260 mm
bn min	= 270 mm
bp min	= 190 mm
H max	= 5510 mm = 6000 mm
Hn min	= 450 mm = 510 mm
Hp	= H - 50 mm
Hpn	= H
W min	= H + 340 mm
α	= 5° + 35°
BxH max	= 32 m ²

FHL high
along roof construction




B max	= 8000 mm
bk min	= 100 mm
b min	= 140 mm
bc min	= 260 mm
bn min	= 270 mm
bp min	= 190 mm
H max	= 4800 mm = 4800 mm = 5800 mm
HL max	= 1320 mm = 3000 mm = 2850 mm
Hn min	= HL+260 mm HL+325 mm HL+360 mm
HL min	= 210 mm
Hp	= H
Hpn	= H
W min	= H - HL+900 mm
α	= 5° + 60°
BxH max	= 32 m ²

HL high




B max	= 8000 mm
bk min	= 100 mm
b min	= 140 mm
bc min	= 280 mm
bn min	= 290 mm
bp min	= 210 mm
H max	= 4800 mm = 4800 mm = 6000 mm
HL max	= 1320 mm = 3000 mm = 2850 mm
Hn min	= HL+260 mm HL+325 mm HL+360 mm
HL min	= 210 mm
Hp	= H
Hpn	= H
W min	= H - HL+750 mm
BxH max	= 41 m ²

HL-K high
on wall brackets



B max	= 5500 mm
bk min	= 140 mm
b min	= 180 mm
bc min	= 300 mm
bn min	= 310 mm
bp min	= 230 mm
H max	= 4800 mm = 5800 mm
HL max	= 3000 mm = 2850 mm
Hn min	= HL+175 mm
HL min	= 800 mm
Hp	= H
Hpn	= H
W min	= H - HL+750 mm
BxH max	= 32 m ²



way of measurement,
view from inside of the room

- B - opening width
- bk - sideroom width
- b min - sideroom width with mounting bracket
- bc - sideroom width on chain mechanism side max 440 mm
- bn - sideroom width on drive side max 440 mm
- bp - jamb width on the side of GFA drive transmission set - max 260
- H - opening height
- Hn - lintel height
- Hp - clear passage height
- Hpn - passage height in door with drive
- HL - lift height
- W - building-in depth
- Wn - building-in depth for drive (400 mm)
- Wc - building-in depth for chain mechanism (270 mm)
- Wp - installation depth for the drive transmission set (1110 mm)
- α - roof angle

order dimension B x H



KRISPOL teollisuusovet valmistetaan yksilöllisesti,
mittatilaus tuotteena.



KRISPOL teollisuusoven takuu 2 vuotta.